



RFP (L)36 IP

SIP-DECT / DECToverIP outdoor base station

The IP 65 outdoor Radio Fixed Part RFP (L)36 IP is connected directly to the LAN like a VoIP device, while using all the benefits of the established DECT technology for radio transmission.

This ensures full compatibility with cordless DECT terminals, which are available as system telephones and standard GAP terminals. The «L» versions come prelicensed for installations of up to 20 RFPs, the technical specification is the same.

The VoIP solution is particularly suitable for branch offices that are connected to a company's headquarter via IP link. The enrolled cordless handsets act as normal company extensions, which means the staff can always be reached on their telephone numbers, regardless of whether they are currently in the headquarter or in one of the branch offices. Using shared IP connections for data and telephony cuts down on the need for additional infrastructure and therefore reduces costs.

RFP (L)36 IP uses built-in dipole antennas. Thus it can be used for the parking sites or delivery areas of a company as well as for a university campus or the outside area of hospitals.



RFP (L)36 IP



Features

DECT

- ✦ All 120 (in America 60) DECT channels supported for maximum use of the DECT capacity
- ✦ 8 simultaneous voice channels per RFP, 4 additional channels for switching purposes
- ✦ GAP standard supported
- ✦ Connection handover in line with the GAP standard
- ✦ DSAA authentication between base and handset
- ✦ Support of DECT encryption
- ✦ Cordless system telephones can use all features offered by the OpenCom 100, 1000 and SIP-DECT
- ✦ Integrated dipole DECT antenna
- ✦ DECT XQ for minimizing interferences in reflecting environments

Service and installation

- ✦ Central configuration
- ✦ Central system journal
- ✦ Central cluster administration
- ✦ Connection via RJ 45
- ✦ Mounting height:
To avoid interferences with other radio equipment, outdoor RFPs must be installed below the roof edge and not higher than 7m above ground.

Ethernet

- ✦ Connection via Ethernet 100/1000 BaseT
- ✦ Power supply in line with Power over Ethernet standard IEEE 802.3af, class 3
- ✦ IPv4

VoIP

- ✦ VoIP connection using RTP/RTCP protocol
- ✦ G.711 / G.722 / G.729AB¹ codec depending on required voice quality and available bandwidth
- ✦ Quality of service supported by DiffServ / ToS Flag
- ✦ Adaptive jitter compensation
- ✦ Echo cancellation / suppression
- ✦ Voice activity detection and comfort noise generator

Technical data

- ✦ Power supply:
Power over Ethernet IEEE 802.3af, class 3
- ✦ Ambient temperature:
-25°C to +55°C
- ✦ Relative humidity:
5 to 95% (non-condensing)
- ✦ Storage temperature:
-5°C to +45°C
- ✦ Type of ingress protection: IP 65
- ✦ Flame resistance UL94 V0
- ✦ Wall and mast mountable
- ✦ Colour: light grey
- ✦ Weight: 995g
- ✦ Dimensions (W x H x D):
240 x 243 x 60 mm

Part numbers RFP (L)36 IP

RFP 36 IP	68635
RFP L36 IP	68621
Wall-mounting set	4602286
Mast-mounting device Ø 65 mm	4602437
Mast-mounting device Ø > 65 mm	4602285

(1) Additional licence required

Aastra Technologies Limited
155 Snow Blvd.
Concord, Ontario Canada
L4K 4N9
www.aastra.com

Copyright © 2013 Aastra Technologies Limited. Aastra and the Aastra logo are trademarks or registered trademarks of Aastra Technologies Limited in the United States, Canada, European Union and other countries. SIP-DECT and DECToverIP are trademarks of Aastra Deutschland GmbH. Picture similar to product. The right for technical modifications is reserved.